ANNEX III

DECLARATION OF PERFORMANCE

N° IND-ALG-00044752

1. Unique identification code of the product-type: **IND-ALG-00044752 (tested by Febenat, vademecum2 p64)** – Cudappah - Lime Black

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

00044752- CTN nr : XXXX xxxxxxx/XXXxxxxxxx – packing CTN : xxxxxxxxx (xx cases) - (xxx,xxm²)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Slabs of natural stone for external paving, Setts of natural stone for external paving, Kerbs of natural stone for external paving, Rough slabs, Modular Tiles, Slabs for floors and stairs, Natural stone masonry units.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

Represented by

Stone Consulting, Gaston Roelandtsstraat 16, 8020 Oostkamp - member S008-02082 of Febenat.

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **na**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **Syst. 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: **na**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **na**

9. Declared performance

Notes to the table: 1. Column 1 shall contain the list of essential characteristics as determined in the harmonised technical specifications for the intended use or uses indicated in point 3 above. 2. For each essential characteristic listed in column 1 and in compliance with the requirements of Article 6, column 2 shall contain the declared performance, expressed by level or class, or in a description, related to the corresponding essential characteristics. The letters 'NPD' (No Performance Determined) shall be indicated where no performance is declared. 3. For each essential characteristic listed in column 1, column 3 shall contain:

(a) dated reference of the corresponding harmonised standard and, where relevant, the reference number of the Specific or Appropriate Technical Documentation used; or (b) dated reference of the corresponding European Assessment Document where available and reference number of the European Technical Assessment used.

Essential characteristics	Norm	Performance				Harmonised technical specification
		E-	Avg.	E+	Unit	
Apparent density	EN 1936		2705		kg/m³	EN 1341:2012 - EN 1342:2012 - EN 1343:2012 – EN 1469:2004 – EN 12057:2004 – EN 12058:2004 – EN 771-6:2005
Open porosity	EN 1936		0,72		vol %	EN 1341:2012 - EN 1342:2012 - EN 1343:2012 – EN 1469:2004 – EN 12057:2004 – EN 12058:2004 – EN 771-6:2005
Compressive strength	EN 1926		247,6		N/mm²	EN 1341:2012 - EN 1342:2012 - EN 1343:2012 – EN 1469:2004 – EN 12057:2004 – EN 12058:2004 – EN 771-6:2005
Flexural strength	EN 12372		48		N/mm²	EN 1341:2012 - EN 1342:2012 - EN 1343:2012 – EN 1469:2004 – EN 12057:2004 – EN 12058:2004 – EN 771-6:2005
Abrasive resistance Capon	EN 14157		22,41		mm	EN 1341:2012 - EN 1342:2012 - EN 1343:2012 – EN 1469:2004 – EN 12057:2004 – EN 12058:2004 – EN 771-6:2005
Frost resistance	EN 12371		56		vis/cycli	EN 1341:2012 - EN 1342:2012 - EN 1343:2012 – EN 1469:2004 – EN 12057:2004 – EN 12058:2004 – EN 771-6:2005
Petrography	EN 12407		Mudstone, dismicriet			EN 1341:2012 - EN 1342:2012 - EN 1343:2012 – EN 1469:2004 – EN 12057:2004 – EN 12058:2004 – EN 771-6:2005
Breaking load	EN 13364		NPD			
Slip resistance	EN 14231		NPD			

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: **na**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

Represented by

Stone Consulting, Gaston Roelandtsstraat 16, 8020 Oostkamp - member S008-02082 of Febenat.

Signed for and on behalf of the manufacturer by:

Julien Vanhollebeke, CEO

Oostkamp 01/04/2013

FILE FROM THE INTERNET